


Front loader T229 – 1300-1600 kg lifting capacity

TYPE	MAXIMUM LIFTING CAPACITY [kg]	LIFTING HEIGHT [mm]	OPERATING PRESSURE [MPa]
T229/1	1300/1600	4000	16
T229	1600	4425	16

Option: MULTILOCK type connection of hydraulic lines.



New shape top connectors and new materials provide improved durability.

The entire structure undergoes a comprehensive corrosion protection process. All parts are subject to shot blasting and degreasing, which provides long lasting corrosion protection.

The loader is equipped with a levelling indicator as standard.



Hydraulic cylinders with a pressure of 20 MPa.




Option: the hydraulic accumulator absorbs shocks to improve operating comfort.

Each pin has a lubricating point.




The KRUS logo confirms the high quality of the machine which ensures increased operating safety.



A top of the line hydraulic control unit is used as standard. The control unit is connected directly to the tractor. It provides rapid and safe operation of the loader. It also protects against failure of the hydraulic pump.

Additional reinforcement inside the outrigger ensures appropriate rigidity of construction.



The main frame (outrigger) is made of sheet metal (5 mm). The selection of fine grain steel and the profile shapes used in the outrigger provide maximum durability and low weight. The design of the outrigger provides optimum visibility from the operator's seat.

The parking jacks of the outrigger are permanently attached to the loader.

The self-lubricated bushes are characterised by superior durability and resistance to wear.



The loader is controlled by joystick providing comfortable and precise operation of the device.



Item	Type	T229-D (long)	T229-1 (short, narrow)	T229-K (short, wide)
1	Maximum lifting capacity [kg]	1600	1300/1600	1300/1600
2	Lifting height [mm]	4425	4000	4000
3	Bucket loading height for bulk materials [mm]	3540	3070	3070
4	Bucket unloading height for bulk materials [mm]	2990	2550	2550
5	Type of lifting cylinder	SCJ90/45/500 SCJ90/45/400	SCJ70/40/500 SCJ70/36/400 S90/45/500 SCJ80/45/400	SCJ70/40/500 SCJ70/36/400 S90/45/500 SCJ80/45/400
6	Operating pressure [MPa]	16	16	16
Weight				
7	Loader [kg]	650	600	600
8	Counterweight + ballast weight [kg]	820	650	650
Frame dimensions				
9	Length [mm]	2700	2300	2300
10	Width [mm]	1040	840	1040
Max speed				
11	Working speed [km/h]	10	10	10
12	Transport speed [km/h]	15	15	15
Optional equipment				
13	Control system	Joystick	Joystick	Joystick
14	Accessory mounts	EURO/SMS	EURO/SMS	EURO/SMS
15	Shock absorber	•	•	•
16	MULTILOCK-type connection of hydraulic lines	•	•	•

Key:
V standard
• optional

The table shows the dimensions of a loader installed on a FARMER F-9258 TE tractor.