


Front loader T248 – 2000 kg load bearing capacity

TYPE	MAXIMUM LIFTING CAPACITY [kg]	LIFTING HEIGHT [mm]	OPERATING PRESSURE [MPa]
T248	2000	3700	18

Option: MULTILOCK type connection of hydraulic lines.



New shape of top connectors and used materials provide greater durability.

The entire structure undergoes complex corrosion protection process. All parts are subject to shot blasting and degreasing, which provides long lasting corrosion protection.




The loader is equipped with a levelling indicator as standard.



The hydraulic lines are located in safe locations.



Hydraulic cylinders with a pressure of 20 MPa.




The hydraulic accumulator absorbs shocks to improve operating comfort.

Each pin has a lubricating point.




Additional reinforcement inside the outrigger ensures appropriate rigidity of construction.



The main frame (of outrigger) is made of metal sheet (4 mm and 6 mm). The selection of fine grain steel and the profile shapes used in the outrigger provide maximum durability and low weight. The design of the outrigger provides optimum visibility from the operator's seat.

The parking jacks of the outrigger are permanently attached to the loader.



A top of the line hydraulic control unit is used as standard. The control unit is connected directly to the tractor. It provides rapid and safe operation of the loader. It also protects against failure of the hydraulic pump.

The self-lubricated bushes are characterised by superior durability and resistance to wear.



The loader is controlled by joystick providing comfortable and precise operation of the device.



Item Type		T248
1	Maximum lifting capacity [kg]	2000
2	Lifting height [mm]	3720
3	Bucket loading height for bulk material [mm]	3458
4	Bucket unloading height for bulk material [mm]	2756
5	Type of lifting cylinder	UCJ415-80/45/690 L UCJ414-80/45/690 P UCJ416-80/45/450
6	Operating pressure [MPa]	18
Weight		
7	Loader [kg]	550
8	Counterweight + ballast weight [kg]	800
Frame dimensions		
9	Length [mm]	2500
10	Width [mm]	1040
Max speed		
11	Working speed [km/h]	10
12	Transport speed [km/h]	15
Optional equipment		
13	Control system	Joystick
14	Accessory mounts	EURO/SMS
15	Shock absorber	V
16	MULTILOCK-type connection of hydraulic lines	•

Key:
V standard
• optional

The table shows the dimensions of a loader installed on a FARMER F-9258 TE tractor.