


# N280 tandem manure spreader – 6T, 8T and 10T

TYPE	CAPACITY	BODY CAPACITY	GROSS COMBINED WEIGHT	TRACTOR POWER OUTPUT
N280	6000 kg	8.1 m <sup>3</sup>	9050 kg	Min. 70 hp
N280/1	8000 kg	8.95 m <sup>3</sup>	11200 kg	Min. 78 hp
N280/2	10000 kg	10.9 m <sup>3</sup>	13600 kg	Min. 80 hp

Wooden floor resistant to damage through contact with manure.




Ladder for easy and secure inspection of the loading process.




Openable and removable side walls for easier loading and extended scope of farm applications.

Adapter shield lifted automatically when the back wall (gate) is raised.



Vertical four-drum adapter with a forward incline.



Screwed-on replaceable teeth made from high-grade steel



Lighting.

Galvanised lower frame.



Connected to the tractor with a hitch.qwd



Manual parking brake.



Mechanical parking jack with a wheel.



Wheel chocks.



Spring tandem wheel system.



Item Type		N280	N280/1	N280/2
1	Load capacity [kg]	6000	8000	10000
2	Body capacity [m <sup>3</sup> ]	8.1	8.95	10.9
<b>Overall dimensions</b>				
3	Length [mm]	6600	6600	7100
4	Width [mm]	2300	2350	2350
5	Height [mm]	2680	2680	2830
<b>Loading space dimensions</b>				
6	Length [mm]	4132	4132	4632
7	Width [mm]	1970	1970	1970
8	Height [mm]	1000	1100	1200
<b>Weight</b>				
9	Kerb weight [kg]	3050	3200	3600
10	Gross combined weight[kg]	9050	11200	13600
<b>Tractor requirements</b>				
11	Power demand [hp]	Min. 70	Min. 78	Min. 80
<b>Adapter characteristics</b>				
12	Type	Vertical with 4 spreading drums		
13	Adapter weight [kg]	450	490	490
14	Adapter drive	Tractor PTO (540 rpm)		
15	Jointed telescopic shaft for adapter drive	540 Nm with friction clutch		
<b>Machine characteristics</b>				
16	Spreading width [mm]	8000-10000		
17	Wheel system	Spring tandem		
18	Wheel track [mm]	1790		
20	Tyres	400-60/15.5 14PR	500-50/17 14PR	
<b>Electrical system</b>				
21	Electrical system voltage [V]	12		
<b>Optional equipment</b>				
22	Hydraulic brake	●		
24	Directional control valve (single-section hydraulics)	●		

Key:

V standard

● Optional