

# N274 and N275 single-axis manure spreader – 10T and 14T

TYPE	CAPACITY	BODY CAPACITY	GROSS COMBINED WEIGHT	TRACTOR POWER OUTPUT
<b>N274</b>	10000 kg	10.6 m <sup>3</sup>	14260 kg	90 hp
<b>N275</b>	14000 kg	12.1 m <sup>3</sup>	18550 kg	100 hp

Folding ladder for easy and secure inspection of the loading process.



Internal back gate lifted hydraulically to 30° in relation to the ground.



Screwed-on replaceable teeth made from high-grade steel.



Vertical two-drum adapter with a forward incline.



Pneumatic double-line brake.



Back shields secured with a cable directly to the arm of the back gate for automatic opening.



Large 600/55x26.5 wheels significantly reduce soil pressing.

Single-axle rigid chassis.



Sprung drawbar (transverse spring).



Hydraulic parking jack.



Adjustable-speed hydraulic drive for the floor conveyor.



Item Type		N274	N275
1	Load capacity [kg]	10000	14000
2	Body capacity [m <sup>3</sup> ]	10.6	12.1
<b>Overall dimensions</b>			
3	Length [mm]	7477	8300
4	Width [mm]	2850	2850
5	Height [mm]	3110	3110
<b>Loading space dimensions</b>			
6	Length [mm]	5000	5750
7	Width [mm]	1500	1500
8	Height (top section) [mm]	1400	1400
<b>Weight</b>			
9	Kerb weight [kg]	4260	4550
10	Gross combined weight [kg]	14260	18550
<b>Tractor requirements</b>			
11	Power demand [hp]	90	100
<b>Adapter characteristics</b>			
12	Type	Vertical with 2 spreading drums	
13	Adapter weight [kg]	920	920
14	Adapter drive	Tractor PTO (1000 rpm)	
15	Jointed telescopic shaft for adapter drive	680 Nm	
<b>Machine characteristics</b>			
16	Spreading width [mm]	12000-15000	
17	Wheel system	Single-axis	
18	Wheel track [mm]	2200	2200
19	Tyres	600/55-26.5	655/65-30.5
<b>Electrical system</b>			
20	Electrical system voltage [V]	12	
<b>Optional equipment</b>			
21	Hydraulic brake		•
22	650/65-30.5 wheels	•	-

Key:  
V standard  
• Optional