

N272/3 VIKING tandem manure spreader – 14T

TYPE	CAPACITY	BODY CAPACITY	GROSS COMBINED WEIGHT	TRACTOR POWER OUTPUT
N272/3	14000 kg	13.4 m ³	20580 kg	135 hp

Gate lift indicator.

Hydraulically lifted back wall (gate) sealed with a rubber element in the lower section.

Mechanical lifting of the shield together with the gate.

Ladder for easier access to the body.

PTO shaft (optional wide-angle shaft).

Tandem chassis on parabolic springs.

Wheels mudguards.

Hydraulically sprung drawbar for connecting with lower hitches of a tractor.

Hydraulic foot.

Hand brake.

Adjustable-speed hydraulic drive for the floor conveyor.

Vertical two-drum adapter with a forward incline. Screwed-in replaceable teeth made of high-grade steel.

Ability to lower and lift the hydraulically actuated top section. This is controlled from the tractor cab.

Shell-shaped loading body.



Item Type		N272/3
1	Load capacity [kg]	14000
2	Body capacity [m ³]	13.4
Overall dimensions		
3	Length [mm]	7890
4	Width [mm]	2550
5	Height [mm]	3390
Loading space dimensions		
6	Length [mm]	5000
7	Width [mm]	2000
8	Height (top section) [mm]	1350 (500)
Weight		
9	Kerb weight [kg]	6580
10	Gross combined weight [kg]	20580
Tractor requirements		
11	Power demand [hp]	135
Adapter characteristics		
12	Type	Vertical with 2 spreading drums
13	Adapter weight [kg]	1020
14	Adapter drive	Tractor PTO (1000 rpm)
15	Jointed telescopic shaft for adapter drive	900 Nm
Machine characteristics		
16	Spreading width [mm]	8000-12 000
17	Wheel system	Tandem-type on parabolic springs
18	Wheel track [mm]	1940
19	Tyres	550/60-22.5 16PR
Electrical system		
20	Electrical system voltage [V]	12
Optional equipment		
21	500 mm high hydraulic top section	•
22	Hydraulic brake	•
23	600/55-22.5 tyres	•
24	Wide-angle shaft	•
25	4-sectional directional control valve	•
26	Scales with an electronic control system	•

Key:
V standard
• Optional