






U818 toothed cultivator – 3 m

TYPE	WEIGHT [kg]	POWER REQUIREMENT [kg]	NO. OF TINES	PACKER ROLLER DIAMETER		
U818	980 kg	80-100 HP	21 pcs	Ø500 mm		

Hydropack installation supported.



Adjustable feet for seeder support.



Aggregation with the tractor using a three-point hitch.

Packer roller (details on page 16).



String rollers with a diameter of 300 mm.



Two rows of spring tines with stepless depth adjustment.



Item Technical data:		U818
1	Working width [m]	3.0
2	Roller type and diameter [mm]	- front: string roller, Ø300 - rear Packer roller, Ø500
3	Working depth [cm]	5-15
4	No. of tines [pcs]	21
5	Tine spacing [mm]	280
6	Working speed [km/h]	7-12
7	Effective field capacity [ha/h]	2.0 - 3.0
8	Hitch [mm]	28/32
9	Suspension category	II or III
10	Power demand [HP]	80-100
11	Weight with Packer roller and hydropack [kg]	980
Overall dimensions		
12	Transport position (hydropack lifted) length / width / height [mm]	3000 / 2160 / 1565
13	Working position length / width / height [mm]	3000 / 1360 / 1800
Sower		
14	Sower type	Row sower
15	Sower width [m]	3.0
16	Overall sower weight [kg]	1200
Optional equipment		
17	Two rows of spring tines with stepless depth adjustment	V
18	Front string rollers	V
19	Hydropack	•

Key:
V standard
• optional